

CLEANER PRODUCT DATA SHEET



PRODUCT & APPLICATION TOOLS



PRODUCT CODE	UNIT SIZE	CONTAINER
	1 gal (3.7 L)	F-style metal can
	5 gal (18.9 L)	Closed head pail

DESCRIPTION

Impermitek's Cleaner is a solvent-based solution specially formulated to clean and reactivate fully cured, in-place Impermitek's primers, membranes, and finishes. The cleaner is also ideal for cleaning tools and for preparing metal and plastic substrates for application of Impermitek's resin components.

ACCESSORY COMPONENTS

The Cleaner is used with General Primer, IR-26 resin, IR-Eco resin, ImpermiGrip, and ImpermiFinish resins.

FEATURES

- Fast drying VOC compliant
- Can be used for cleaning with various Impermitek products

STORAGE

Always store closed containers in a cool, ventilated, and dry location, away from ignition sources, heat, reducing agents, strong oxidizers, alkalis, accelerators, and pressurized containers. Do not store in direct sunlight or in temperatures below 32°F (0°C) or above 77°F (25°C). Do not allow this material to freeze. Approximate maximum shelf life is 12 months when properly stored.

Materials stored on project sites during application should be kept on a pallet in a shaded, well-ventilated area. In unshaded areas, materials should be covered with a white, reflective tarp in a manner that allows for air circulation beneath the tarp.

TECHNICAL DATA

Property*	Value	Test Method
Technology	Solvent	-
Color	Clear	-
Flash Point °F (°C)	6 (-14)	ASTM D93
Dry Time @68°F (20°C)**	20 min	-
Max. Next Coat Time @ 68°F (20°C)**	60 min	-
Shelf Life (months)	12	-
VOC Content (g/L)	<5	EPA Method 24

* Data is represented by average values, unless noted otherwise.

** All working and cure times are approximate and may vary upon wind, humidity and ambient/surface temperatures.

USE

Apply the Cleaner using clean white lint-free cloth rags. Thoroughly wipe down the cured resin or membrane surface and allow the area to dry for approximately 20 minutes. Once clean, Apply the next Impermitek component within 60 minutes.

SAFETY & HANDLING

Please, refer to the relevant Safety Data Sheet (SDS) prior to handling or use. Use materials in strict accordance with published recommendations. Dispose of waste materials in accordance with local, state, and federal regulations.

TECHNICAL ASSISTANCE

For further information, please contact Impermitek Technical Services at +1 (780) 906-4600 or technical@impermitek.com. More information can also be found at www.impermitek.com.

Please, refer to the Impermitek installation recommendations, application manuals, and guide specifications, for complete information regarding the suitability, application, use, and handling of Impermitek products.