

GP (GENERAL PRIMER) ACCELERATOR PRODUCT DATA SHEET



PRODUCT & APPLICATION TOOLS



PRODUCT CODE	UNIT SIZE	MIXING RATIO
158103-SC	0.13 Gal (0.5 L)	1 unit per can of General Primer

DESCRIPTION

Impermitek's GP Accelerator is an additive that speeds up curing time to shorten pot-life when applying Impermitek's General Primer in low temperature ambients.

ACCESSORY COMPONENTS

The GP Accelerator may be used with the following Impermitek resin:

- General Primer

FEATURES

- Low VOC formulation
- Easily mixes with the General Primer

STORAGE

Always store closed containers in a cool, ventilated and dry location away from heat and oxidizing agents. Do not store in direct sunlight or in temperatures at or below 32°F (0°C) or above 77°F (25°C). Approximate maximum shelf life is 12 months when properly stored, sealed, and unmixed.

WARNINGS

When using the General Primer, the Accelerator is recommended when ambient temperatures are from 41° to 50°F (5° - 10°C) and **required** when from 34° to 40°F (1° - 4°C).

The GP accelerator should only be used with the General Primer Resin, as recommended.

MIXING

Add the entire contents of the GP Accelerator into a 2.64 gallon (10 L) can of General Primer. Thoroughly mix the entire drum for 3 minutes, or as required, using a slow-speed mechanical mixer fitted with a spiral agitator at 200–400 rpm. Ensure the additive is fully incorporated while avoiding aeration of the resin.

Refer to specific product data sheets for additional instructions and information regarding mixing, catalyzation, and application for individual products.

SAFETY & HANDLING

Please refer to the relevant Safety Data Sheet (SDS) prior to handling or use. Use materials in strict accordance with published guidelines. Dispose of waste materials in accordance with local, state and federal regulations.

TECHNICAL ASSISTANCE

For further information, please contact Impermitek Technical Services at +1 (780) 906-4600 or **technical@impermitek.com**. More information can also be found at www.impermitek.com.

Please, refer to the Impermitek installation recommendations, application manuals, and guide specifications, for complete information regarding the suitability, application, use, and handling of Impermitek products.