

PMMA PIGMENT PRODUCT DATA SHEET



APPLICATION TOOL



PRODUCT CODE	UNIT SIZE	APPROXIMATE COVERAGE
162205-SC	0.06 gal (0.22 L)	1 unit per 4 gal IR-26

***Note:** See reference chart for color number (#).

DESCRIPTION

PMMA Pigment is a resin pigment additive for use with Impermitek ImpermiFinish Unpigmented resin.

ACCESSORY COMPONENTS

Impermitek's PMMA Pigment requires ImpermiFinish Unpigmented Resin.

CODE	ITEM	PACK SIZE
130012-SC	ImpermiFinish Unpigmented	2.16 gal/8.17L (8.5 kg)

FEATURES

- Non-toxic low odor
- Pre-measured for easy mixing
- UV stabilized with excellent color fastness
- Available in stock & customer colors

STORAGE

Always store closed containers in a cool, ventilated and dry location away from heat and oxidizing agents. Do not store in direct sunlight or in temperatures at or below 32°F (0°C) or above 77°F (25°C). Approximate maximum shelf life is 12 months when properly stored, sealed, and unmixed.

WARNINGS

PMMA Pigment should only be used with ImpermiFinish Unpigmented resin. Once mixed with ImpermiFinish Unpigmented resin, follow the limitations required or recommended for

ImpermiFinish and ImpermiFinish Unpigmented resins.

***NOTES:** Combining the color additive to ImpermiFinish Unpigmented resins does not affect pot life or cure time of the product.

The IR-26 High Temp Inhibitor should only be used as recommended with the above specified Impermitek resins.

MIXING

One pouch of PMMA Pigment is required for each container of ImpermiFinish Unpigmented resin. Do not decant ImpermiFinish Unpigmented resin from its original container prior to adding the pigment to ensure the correct ratio of pigment to resin.

The ImpermiFinish Unpigmented resin should be thoroughly mixed before adding the color additive. Using a slow-speed (200 to 400 rpm) mechanical agitator, thoroughly mix the entire container of resin for +/-4 minutes. Add the entire contents of the Pigment pouch to the liquid resin and continue mixing for 2 - 5 minutes until uniform streak-free color is achieved.

IMPORTANT: Do not add the Impermitek Catalyst Powder to the ImpermiFinish resin until the PMMA Pigment has been fully mixed in. This will ensure maximum pot life and minimize wastage during installation.

SAFETY & HANDLING

Please refer to the relevant Safety Data Sheet (SDS) prior to handling or use. Use materials in strict accordance with published guidelines. Dispose of waste materials in accordance with local, state and federal regulations.

TECHNICAL ASSISTANCE

For further information, please contact Impermitek Technical Services at +1 (780) 906-4600 or technical@impermitek.com. More information can also be found at www.impermitek.com.

Please, refer to Impermitek's installation recommendations, application manuals, and guide specifications for complete information regarding the suitability, application, use, and handling of Impermitek products.

PMMA PIGMENT
PRODUCT DATA SHEET



PMMA PIGMENT
PRODUCT DATA SHEET

