

# SL MORTAR PART A (RESIN) PRODUCT DATA SHEET



## PRODUCT & APPLICATION TOOLS



| Product Code              | Unit Size                   | Approximate Coverage  |
|---------------------------|-----------------------------|-----------------------|
| 122103-SC<br>Summer Resin | 10 kg<br>2.64 gal<br>(10 L) | 1 Can per<br>Workpack |
| 122105-SC<br>Winter Resin |                             |                       |

## DESCRIPTION

Impermitek's SL (Self-Leveling) Mortar Part A is a high-performance rapid setting, polymethyl methacrylate (PMMA) resin utilized in conjunction with Impermitek's SL Mortar Part B (Filler) to create Impermitek's SL Mortar. The SL Mortar Part A is available in both a summer and winter formulas.

## ACCESSORY COMPONENTS

The SL Mortar is created by combining Impermitek's Self-Leveling Mortar Part A Resin and Part B Filler. The SL Mortar also requires Impermitek's Catalyst Powder for curing.

| CODE      | ITEM                      | PACK SIZE       |
|-----------|---------------------------|-----------------|
| 122104-SC | SL Mortar Part B (Filler) | 50.7 lb (23 kg) |
| 102031-SC | Catalyst Powder (Pail)    | 4.4 lb (2 kg)   |
| 102030    | Catalyst Powder (Box)     | 55 lb (25 kg)   |

## FEATURES

- Low VOC resin formulation
- Excellent chemical resistance
- Fast Curing from 60 to 75 minutes when used in the SL Mortar

## STORAGE

Always store closed containers in a cool, ventilated and dry location away from heat and oxidizing agents. Do not store in direct sunlight or in temperatures at or below 32°F (0°C) or above 77°F (25°C). Approximate maximum shelf life is 12 months when properly stored, sealed, and unmixed.

## WARNINGS

The SL Mortar Part A should only be used with the SL Mortar Part B (Filler). Once mixed with the Self-Leveling Mortar Part-B (filler), follow the limitations required or recommended for Impermitek SL Mortar.

**\*Note:** Combining Impermitek SL Mortar Part-A and Part-B does not affect pot life or cure time of these products.

## MIXING & APPLICATION

See Impermitek's SL Mortar product data sheet for recommend mixing, catalyzation, and application recommendations and guidelines.

## SAFETY & HANDLING

Please refer to the relevant Safety Data Sheet (SDS) prior to handling or use. Use materials in strict accordance with published recommendations. Dispose of waste materials in accordance with local, state and federal regulations.

## TECHNICAL ASSISTANCE

For further information, please contact Impermitek Technical Services at +1 (780) 906-4600 or [technical@impermitek.com](mailto:technical@impermitek.com). More information can also be found at [www.impermitek.com](http://www.impermitek.com).

Please, refer to the Impermitek installation recommendations, application manuals, and guide specifications, for complete information regarding the suitability, application, use, and handling of Impermitek products