

Catalyst Powder

Impermitek

Version No: 2.3

Safety Data Sheet according to WHMIS 2023 requirements

Initial Date: 15/05/2022
Revision Date: 18/11/2024
Print Date: 05/12/2025
S.GHS.CAN.EN

SECTION 1 Identification

Product name	Catalyst Powder
Synonyms	Not Available
Proper shipping name	ORGANIC PEROXIDE TYPE D, SOLID (contains dibenzoyl peroxide)

Recommended use of the chemical and restrictions on use

Relevant identified uses	Catalyst for use with liquid applied roof waterproofing systems
--------------------------	---

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	Impermitek
Address	5031 53 Ave, Mundare, AB, T0B 3H0, Canada
Telephone	+1 780 289 4542 or +1 780 906 4600
Fax	Not Available
Website	www.impermitek.com
Email	technical@impermitek.com

Emergency phone number

Association / Organisation	Canutec
Emergency telephone numbers	1-888-226-8832 (Canada and US)
Other emergency telephone numbers	1-613-996-6666 (International)

SECTION 2 Hazard(s) identification

Classification of the substance or mixture

NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Canadian WHMIS Symbols



Classification	Organic Peroxides Type D, Sensitisation (Skin) Category 1, Reproductive Toxicity Category 1B, Hazardous to the Aquatic Environment Acute Hazard Category 1, Hazardous to the Aquatic Environment Long-Term Hazard Category 1
----------------	--

Label elements

Hazard pictogram(s)	
---------------------	--

Signal word	Danger
-------------	---------------

Hazard statement(s)

H242	Heating may cause a fire.
H317	May cause an allergic skin reaction.
H360	May damage fertility or the unborn child.
H410	Very toxic to aquatic life with long lasting effects.

Physical and Health hazard(s) not otherwise classified

Not Applicable

Precautionary statement(s) Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P234	Keep only in original packaging.

Precautionary statement(s) Response

P308+P313	IF exposed or concerned: Get medical advice/ attention.
-----------	---

Precautionary statement(s) Storage

P403	Store in a well-ventilated place.
P405	Store locked up.
P411	Store at temperatures not exceeding 25°C

Precautionary statement(s) Disposal

No further product hazard information.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
94-36-0	49-51	<u>dibenzoyl peroxide</u>
84-61-7	40-50	<u>dicyclohexyl phthalate</u>

SECTION 4 First-aid measures

Description of first aid measures

Eye Contact	If this product comes in contact with the eyes: ▶ Immediately hold the eyelids apart and flush the eye with 2% sodium carbonate solution or 5% sodium ascorbate solution then wash continuously for at least 15 minutes with fresh running water. ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▶ Transport to hospital (or doctor) without further delay. ▶ Removal of contact lenses should only be undertaken by trained personnel.
Skin Contact	If skin contact occurs: ▶ Immediately remove all contaminated clothing, including footwear. ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation.
Inhalation	▶ If fumes or combustion products are inhaled remove from contaminated area. ▶ Lay patient down. Keep warm and rested. ▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. ▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. ▶ Transport to hospital, or doctor, without delay.
Ingestion	▶ Immediately give a glass of water. ▶ First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Toxic myocarditis may follow ingestion of oxidizing agents such as peroxides.

BASIC TREATMENT

- Establish a patent airway with suction where necessary.
- Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- Administer oxygen by non-rebreather mask at 10 to 15 l/min.
- Monitor and treat, where necessary, for pulmonary oedema .
- Monitor and treat, where necessary, for shock.
- Anticipate seizures .
- DO NOT use emetics.** Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.
- DO NOT attempt neutralisation as exothermic reaction may occur.**
- Skin burns should be covered with dry, sterile bandages, following decontamination.

ADVANCED TREATMENT

- Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- Positive-pressure ventilation using a bag-valve mask might be of use.
- Monitor and treat, where necessary, for arrhythmias.
- Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- Drug therapy should be considered for pulmonary oedema.
- Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- Treat seizures with diazepam.
- Proparacaine hydrochloride should be used to assist eye irrigation.

BRONSTEIN, A.C. and CURRANCE, P.L.
EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

SECTION 5 Fire-fighting measures

Extinguishing media

- FOR **SMALL FIRE**:
- Water spray, foam, CO2 or dry chemical.
 - DO NOT** use water jets.
- FOR **LARGE FIRE**:
- Flood fire area with water from a distance.

Special hazards arising from the substrate or mixture

Fire Incompatibility	- Avoid storage with reducing agents. - Avoid any contamination of this material as it is very reactive and any contamination is potentially hazardous
----------------------	--

Special protective equipment and precautions for fire-fighters

Fire Fighting	- Alert Fire Brigade and tell them location and nature of hazard. - May be violently or explosively reactive. - Wear full body protective clothing with breathing apparatus. - Prevent, by any means available, spillage from entering drains or water courses.
Fire/Explosion Hazard	- Will not burn but increases intensity of fire. - May explode from friction, shock, heat or containment. - Heating may cause expansion or decomposition leading to violent rupture of containers. - Heat affected containers remain hazardous. carbon dioxide (CO2) other pyrolysis products typical of burning organic material. - Benzoyl peroxide decomposes when heated with formation of dense white toxic smoke of benzoic acid, phenyl benzoate, terphenyls, biphenyls, and carbon dioxide. - Organic peroxides provide internal oxygen for combustion, so burn intensely. - Simple smothering actions are not effective against established fires. NOTE: A Type D Organic Peroxide: - may partially detonate - does not deflagrate rapidly and - shows no violent effect when heated under confinement

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	- Clean up all spills immediately. - No smoking, naked lights, ignition sources. - Avoid all contact with any organic matter including fuel, solvents, sawdust, paper or cloth and other incompatible materials, as ignition may result. - Avoid breathing dust or vapours and all contact with skin and eyes.
Major Spills	- Clear area of personnel and move upwind. - Alert Fire Brigade and tell them location and nature of hazard. - May be violently or explosively reactive. - Wear full body protective clothing with breathing apparatus.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Safe handling	▶ Mix only as much as is required ▶ DO NOT return the mixed material to original containers For oxidisers, including peroxides. · Avoid personal contact and inhalation of dust, mist or vapours. · Provide adequate ventilation. · Always wear protective equipment and wash off any spillage from clothing.
Other information	▶ Store in original containers in an isolated approved flammable materials storage area. ▶ Keep containers securely sealed as supplied. ▶ WARNING: Gradual decomposition during storage in sealed containers may lead to a large pressure build-up and subsequent explosion. ▶ No smoking, naked lights, heat or ignition sources. FOR MINOR QUANTITIES: Ensure that: ▶ packages are not opened in storage area, ▶ the goods are kept at least 3 metres from sources of heat as well as all other dangerous goods and all other materials which might react with this material might react to cause a fire, a chemical reaction or explosion, ▶ materials for absorbing and neutralising spills are kept near the storage; ▶ procedures are displayed at the storage describing actions to be taken in the event of a spill or fire. ▶ adequate numbers and types of portable fire extinguisher are provided in or near the storage area. FOR PACKAGE STORAGE: ▶ If the material is stored in an indoor fireproof cabinet, the cabinet must be vented to outside the building containing the cabinet. ▶ Packages must be protected from exposure to weather unless the packages are: (i) sole packages of more than 20 l capacity (ii) of metallic or plastic construction (iii) securely closed and are not to be opened in the storage area (iv) stored in such a manner that rain water, contaminated with the material, is collected and disposed of safely.

Conditions for safe storage, including any incompatibilities

Suitable container	▶ Metal packagings meeting the test criteria of Packing Group I, must NOT be used; this avoids unnecessary confinement. ▶ Packagings for organic peroxides must be constructed so that none of the materials, which are in contact with the contents, will catalyse or otherwise dangerously affect the properties of their contents. ▶ For combination packages, cushioning materials must not be readily combustible and must NOT cause decomposition of the organic peroxide if leakage occurs. ▶ Generally only stainless steel 316, polyethylene or glass lined equipment is suitable for use when working with organic peroxides. ▶ Some plastics may be incompatible with this material, check with manufacturer for storage suitability. ▶ DO NOT repack. Use containers supplied by manufacturer only. ▶ Check that containers are clearly labelled ▶ Type D Solid Organic Peroxides, UN 3106, UN 3116 are to be packed to the requirements of Packing method OP7B of the ADG Code, with maximum mass of 50 kg. ▶ Steel, Aluminium, Plastic drum / container or plastic inner receptacle in fibre-board or metal outer container.
Storage incompatibility	For benzoyl peroxide: ▶ Avoid reaction with acids, alkalis, oxidising and reducing agents, metals and metal oxides, and combustible materials. ▶ Amines and solutions of cobalt salts used as promoters and accelerators in polyester compounds if mixed with benzoyl peroxide will cause spontaneous decomposition (detonation). ▶ Alkalis cause rapid decomposition of benzoyl peroxide with generation of large volumes of carbon dioxide gas (CO2) and may pressurise containers. ▶ Avoid contact with copper, brass, lead and zinc. Phthalates: ▶ react with strong acids, strong oxidisers, permanganates and nitrates ▶ attack some form of plastics ▶ As a class, organic peroxides are amongst the most hazardous materials commonly used in the workplace or laboratory. Several are highly flammable and extremely sensitive to shock, heat, spark, friction, impact and light and readily react with strong oxidising and reducing agents. ▶ Organic compounds, especially finely divided materials, can ignite on contact with concentrated peroxides. ▶ Strongly reduced material such as sulfides, nitrides, and hydrides may react explosively with peroxides. ▶ Incidents involving interaction of active oxidants and reducing agents, either by design or accident, are usually very energetic and examples of so-called redox reactions. ▶ Organic peroxides as a class are highly reactive. ▶ They are thermally unstable and prone to undergoing exothermic self-accelerating decomposition. ▶ Organic peroxides may decompose explosively, burn rapidly, be impact and/or friction sensitive and react dangerously with many other substances. ▶ Amines and polyester accelerators (cobalt salts, for example) if mixed with organic peroxides / organic peroxide mixtures will cause rapid / spontaneous decomposition with fire / explosion hazard. ▶ Avoid any contamination. ▶ Avoid finely divided combustible materials ▶ Avoid all external heat. ▶ Avoid mixing or reaction with acids, alkalies, reducing agents, metal powders, metal oxides, transition metals and their compounds. ▶ Avoid storage with reducing agents. ▶ Peroxides decompose over time and give off oxygen. ▶ Peroxides require controlled storage for stability. ▶ DANGER: Explosion hazard, never mix peroxides with accelerators or promoters. ▶ Avoid any contamination of this material as it is very reactive and any contamination is potentially hazardous

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	dibenzoyl peroxide	Benzoyl peroxide	5 mg/m3	5 mg/m3	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	dibenzoyl peroxide	Benzoyl peroxide	5 mg/m3	10 mg/m3	Not Available	Not Available

Catalyst Powder

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Canada - Manitoba Occupational Exposure Limits	dibenzoyl peroxide	Not Available	5 mg/m3	Not Available	Not Available	TLV® Basis: URT & skin irr
Canada - Prince Edward Island Occupational Exposure Limits	dibenzoyl peroxide	Benzoyl peroxide	5 mg/m3	Not Available	Not Available	TLV® Basis: URT & skin irr
Canada - British Columbia Occupational Exposure Limits	dibenzoyl peroxide	Benzoyl peroxide	5 mg/m3	Not Available	Not Available	Not Available
Canada - Ontario Occupational Exposure Limits	dibenzoyl peroxide	Particles (Insoluble or Poorly Soluble) Not Otherwise Specified (PNOS) (Inhalable fraction)	10 mg/m3	Not Available	Not Available	(I) Inhalable fraction: means that size fraction of the airborne particulate deposited anywhere in the respiratory tract and collected during air sampling with a particle size-selective device that, (a) meets the ACGIH particle size-selective sampling criteria for airborne particulate matter; and (b) has the cut point of 100 µm at 50 per cent collection efficiency.
Canada - Ontario Occupational Exposure Limits	dibenzoyl peroxide	Particles (Insoluble or Poorly Soluble) Not Otherwise Specified (PNOS) (Respirable fraction)	3 mg/m3	Not Available	Not Available	(R) Respirable fraction: means that size fraction of the airborne particulate deposited in the gas-exchange region of the respiratory tract and collected during air sampling with a particle size-selective device that, (a) meets the ACGIH particle size-selective sampling criteria for airborne particulate matter; and (b) has the cut point of 4 µm at 50 per cent collection efficiency.
Canada - Alberta Occupational Exposure Limits	dibenzoyl peroxide	Benzoyl peroxide	5 mg/m3	Not Available	Not Available	3 - Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required.
Canada - Alberta Occupational Exposure Limits	dibenzoyl peroxide	Dibenzoyl peroxide (Benzoyl peroxide)	5 mg/m3	Not Available	Not Available	3 - Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required.
Canada - Northwest Territories Occupational Exposure Limits	dibenzoyl peroxide	Benzoyl peroxide	5 mg/m3	10 mg/m3	Not Available	Not Available
Canada - Quebec Permissible Exposure Values for Airborne Contaminants	dibenzoyl peroxide	Benzoyl peroxide	5 mg/m3	Not Available	Not Available	Not Available
Canada - Nova Scotia Occupational Exposure Limits	dibenzoyl peroxide	Benzoyl peroxide	5 mg/m3	Not Available	Not Available	TLV Basis: upper respiratory tract & skin irritation

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard 'physically' away from the worker and ventilation that strategically 'adds' and 'removes' air in the work environment.
Individual protection measures, such as personal protective equipment	
Eye and face protection	▶ Chemical goggles. ▶ Full face shield may be required for supplementary but never for primary protection of eyes. ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.
Skin protection	See Hand protection below
Hands/feet protection	▶ Wear chemical protective gloves, e.g. PVC. ▶ Wear safety footwear or safety gumboots, e.g. Rubber NOTE: ▶ The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact. ▶ Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed. ▶ DO NOT wear cotton or cotton-backed gloves. ▶ DO NOT wear leather gloves. ▶ Promptly hose all spills off leather shoes or boots or ensure that such footwear is protected with PVC over-shoes.
Body protection	See Other protection below
Other protection	▶ Overalls. ▶ PVC Apron. ▶ PVC protective suit may be required if exposure severe. ▶ Eyewash unit.

Continued...

Catalyst Powder

- ▶ Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity.
- ▶ For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets).
- ▶ Non sparking safety or conductive footwear should be considered. Conductive footwear describes a boot or shoe with a sole made from a conductive compound chemically bound to the bottom components, for permanent control to electrically ground the foot and shall dissipate static electricity from the body to reduce the possibility of ignition of volatile compounds.

Respiratory protection

Respiratory protection is only required in the likelihood that relevant exposure limits may be approached or exceeded, e.g. application in enclosed spaces with restricted air exchange. Concentrations of potentially hazardous substances in air will remain low during normal outdoor application and will not pose a risk to the applicator.

Type -P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

- Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.
- The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure - ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).
- Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.
- Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.
- Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU)
- Use approved positive flow mask if significant quantities of dust becomes airborne.
- Try to avoid creating dust conditions.

Class P2 particulate filters are used for protection against mechanically and thermally generated particulates or both.

P2 is a respiratory filter rating under various international standards, Filters at least 94% of airborne particles

Suitable for:

- Relatively small particles generated by mechanical processes eg. grinding, cutting, sanding, drilling, sawing.
- Sub-micron thermally generated particles e.g. welding fumes, fertilizer and bushfire smoke.
- Biologically active airborne particles under specified infection control applications e.g. viruses, bacteria, COVID-19, SARS

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance/Colour	White		
Physical state	Solid	Relative density (Water = 1)	1.23
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	SADT 55
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available
Heat of Combustion (kJ/g)	Not Available	Ignition Distance (cm)	Not Available
Flame Height (cm)	Not Available	Flame Duration (s)	Not Available
Enclosed Space Ignition Time Equivalent (s/m3)	Not Available	Enclosed Space Ignition Deflagration Density (g/m3)	Not Available
Particle Characteristics	Not Available		

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	▶ Unstable in the presence of incompatible materials. ▶ Product is considered stable under normal handling conditions. ▶ Prolonged exposure to heat. ▶ Hazardous polymerisation will not occur. NOTE: ▶ A range of exothermic decomposition energies for peroxides is given as 200-340 kJ/mol. ▶ The relationship between energy of decomposition and processing hazards has been the subject of discussion; it is suggested that values of energy releases per unit of mass, rather than on a molar mass basis (J/g) be used in the assessment. For example, in open vessel processes (with man-hole size openings, in an industrial setting), substances with exothermic decomposition energies below 500 J/g are unlikely to present a danger, whilst those in closed vessel processes (opening is a safety valve or bursting disk) present some danger where the decomposition energy exceeds 150 J/g. BREITHERICK: Handbook of Reactive Chemical Hazards, 4th Edition
Possibility of hazardous reactions	See section 7

Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

a) Acute Toxicity	Based on available data, the classification criteria are not met.
b) Skin Irritation/Corrosion	Based on available data, the classification criteria are not met.
c) Serious Eye Damage/Irritation	Based on available data, the classification criteria are not met.
d) Respiratory or Skin sensitisation	There is sufficient evidence to classify this material as sensitising to skin or the respiratory system
e) Mutagenicity	Based on available data, the classification criteria are not met.
f) Carcinogenicity	Based on available data, the classification criteria are not met.
g) Reproductivity	There is sufficient evidence to classify this material as toxic to reproductivity
h) STOT - Single Exposure	Based on available data, the classification criteria are not met.
i) STOT - Repeated Exposure	Based on available data, the classification criteria are not met.
j) Aspiration Hazard	Based on available data, the classification criteria are not met.

Inhaled	The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. The inhalation of organic peroxide dusts or vapours can produce throat and lung irritation and cause an asthma-like effect. Over-exposure can cause tears, salivation, lethargy, slow breathing, breathing difficulties, headache, weakness, tremor, stupor and swelling of the lung.
Ingestion	Ingestion of organic peroxides may produce nausea, vomiting, abnormal pain, stupor, bluish discoloration of skin and mucous membranes. Inflammation of the heart muscle may also occur. The material has NOT been classified by EC Directives or other classification systems as 'harmful by ingestion'. This is because of the lack of corroborating animal or human evidence. The toxicity of phthalates is not excessive due to slow oral absorption and metabolism. Absorption is affected by fat in the diet. Repeated doses can cause cumulative toxic effects, and symptoms include an enlarged liver which often reverses if exposure is maintained. Carbohydrate metabolism is disrupted, and cholesterol and triglyceride levels in the blood falls.
Skin Contact	The material may accentuate any pre-existing dermatitis condition Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. All organic peroxides are irritating to the skin and if allowed to remain on the skin, may produce inflammation; some are allergenic. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. There is some evidence to suggest that the material may cause mild but significant inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering.
Eye	Eye contact with organic peroxides can cause clouding, redness, swelling and burns of the eye on prolonged contact. Evidence exists, or practical experience predicts, that the material may cause eye irritation in a substantial number of individuals. Prolonged eye contact may cause inflammation characterised by a temporary redness of the conjunctiva (similar to windburn).
Chronic	Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems. Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population. Ample evidence exists, from results in experimentation, that developmental disorders are directly caused by human exposure to the material. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. Exposure to phthalates over years leads to pain, numbness and spasms in the hands and feet. Many people have developed multiple disorders in the nervous system and the balancing system. Prolonged or repeated skin contact with benzoyl peroxide may result in allergic skin reactions even at diluted concentrations. Ingestion results in abdominal pain, low body oxygen and severe depression. Chronic effects of exposure include allergic reactions characterised by redness, itching, oozing, crusting, and scaling of the skin and asthmatic wheezing. Although it does not exhibit complete carcinogenic or tumour-initiating activity, it has been associated with certain tumours of like papillomas and squamous cell carcinomas. There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment. Persistent exposure over a long period of time to peroxides produces allergic skin reactions (redness and scaling of the skin) and asthmatic wheezing.

Powder Catalyst	<table><tr><th>TOXICITY</th><th>IRRITATION</th></tr><tr><td>Not Available</td><td>Not Available</td></tr></table>		TOXICITY	IRRITATION	Not Available	Not Available												
	TOXICITY	IRRITATION																
Not Available	Not Available																	
dibenzoyl peroxide	<table><tr><th>TOXICITY</th><th>IRRITATION</th></tr><tr><td>dermal (mammal) LD50: >1000 mg/kg^[2]</td><td>Eye (Rodent - rabbit): 500mg/24H - Mild</td></tr><tr><td>Oral (Rat) LD50: 7710 mg/kg^[2]</td><td>Eye: adverse effect observed (irritating)^[1]</td></tr><tr><td></td><td>Skin (Human - woman): 1% - Moderate</td></tr><tr><td></td><td>Skin (Human): 0.5%</td></tr><tr><td></td><td>Skin (Human): 5%/48H</td></tr><tr><td></td><td>Skin (Human): 5%/8W(intermittent) - Severe</td></tr><tr><td></td><td>Skin: no adverse effect observed (not irritating)^[1]</td></tr></table>		TOXICITY	IRRITATION	dermal (mammal) LD50: >1000 mg/kg ^[2]	Eye (Rodent - rabbit): 500mg/24H - Mild	Oral (Rat) LD50: 7710 mg/kg ^[2]	Eye: adverse effect observed (irritating) ^[1]		Skin (Human - woman): 1% - Moderate		Skin (Human): 0.5%		Skin (Human): 5%/48H		Skin (Human): 5%/8W(intermittent) - Severe		Skin: no adverse effect observed (not irritating) ^[1]
	TOXICITY	IRRITATION																
	dermal (mammal) LD50: >1000 mg/kg ^[2]	Eye (Rodent - rabbit): 500mg/24H - Mild																
	Oral (Rat) LD50: 7710 mg/kg ^[2]	Eye: adverse effect observed (irritating) ^[1]																
		Skin (Human - woman): 1% - Moderate																
		Skin (Human): 0.5%																
		Skin (Human): 5%/48H																
		Skin (Human): 5%/8W(intermittent) - Severe																
		Skin: no adverse effect observed (not irritating) ^[1]																
dicyclohexyl phthalate	<table><tr><th>TOXICITY</th><th>IRRITATION</th></tr><tr><td>dermal (rat) LD50: >2000 mg/kg^[1]</td><td>Eye: no adverse effect observed (not irritating)^[1]</td></tr><tr><td>Oral (Rat) LD50: >2000 mg/kg^[1]</td><td>Skin: no adverse effect observed (not irritating)^[1]</td></tr></table>		TOXICITY	IRRITATION	dermal (rat) LD50: >2000 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]	Oral (Rat) LD50: >2000 mg/kg ^[1]	Skin: no adverse effect observed (not irritating) ^[1]										
TOXICITY	IRRITATION																	
dermal (rat) LD50: >2000 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]																	
Oral (Rat) LD50: >2000 mg/kg ^[1]	Skin: no adverse effect observed (not irritating) ^[1]																	

Legend:

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

DIBENZOYL PEROXIDE	The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing.
DICYCLOHEXYL PHTHALATE	DCHP can be considered to have low acute toxicity. It causes minimal irritation of the skin and eye. It may also cause wheezing. Animal testing suggests that repeated exposure may cause increased weight of the liver. Available data indicate that phthalate esters are minimally toxic by swallowing, inhalation and skin contact. Repeated exposure may result in weight gain, liver enlargement and induction of liver enzymes. They may also cause shrinking of the testicles and other structural malformations. They may reduce male and female fertility and number of live births, according to animal testing.
Catalyst Powder & DICYCLOHEXYL PHTHALATE	Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. The material may produce peroxisome proliferation. Peroxisomes are single, membrane limited organelles in the cytoplasm that are found in the cells of animals, plants, fungi, and protozoa.
Catalyst Powder & DIBENZOYL PEROXIDE & DICYCLOHEXYL PHTHALATE	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions.
Catalyst Powder & DIBENZOYL PEROXIDE	Benzoyl peroxide may cause double vision, breathing problems, excess saliva and tear formation, redness of the skin and changes in motor activity. It did not produce blood or biochemical adverse effects, gene mutation or evidence of cancer. Repeated oral administration may result in decreased weights of testes and the newborn.

Acute Toxicity	✗	Carcinogenicity	✗
Skin Irritation/Corrosion	✗	Reproductivity	✓
Serious Eye Damage/Irritation	✗	STOT - Single Exposure	✗
Respiratory or Skin sensitisation	✓	STOT - Repeated Exposure	✗
Mutagenicity	✗	Aspiration Hazard	✗

Legend:

✗ – Data either not available or does not fill the criteria for classification

✓ – Data available to make classification

SECTION 12 Ecological information

Toxicity					
Catalyst Powder	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
dibenzoyl peroxide	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	0.042mg/l	2
	EC50	48h	Crustacea	0.11mg/l	2
	EC10(ECx)	504h	Crustacea	0.001mg/l	2
	LC50	96h	Fish	0.06mg/l	2
dicyclohexyl phthalate	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	>2mg/l	2
	LC50	96h	Fish	>2mg/l	2
	NOEC(ECx)	504h	Crustacea	0.181mg/l	2
Legend:		Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. US EPA, Ecotox database - Aquatic Toxicity Data 4. ECETOC Aquatic Hazard Assessment Data 5. NITE (Japan) - Bioconcentration Data 6. METI (Japan) - Bioconcentration Data 7. Vendor Data			

Very toxic to aquatic organisms.
Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.
Wastes resulting from use of the product must be disposed of on site or at approved waste sites.
For benzoyl peroxide:
Benzoyl peroxide has a melting point of 104 -106 °C, vapor pressure of 0.00929 Pa, solubility of 9.1 mg/L in water at 25 C, and log Pow of 3.43 at 25 C.
Environmental Fate: For indirect photolysis in the atmosphere, the half-life is estimated to be 3 days. The substance is readily biodegradable and hydrolyses rapidly in water. The main hydrolysis product of benzoyl peroxide is benzoic acid.
For Phthalate Esters:
Terrestrial Fate: Phthalate esters have been observed to broken down by a wide range of bacteria. Biodegradation is, therefore, expected to be the dominant fate in surface soils and sediments.
Little information is available on the fate of phthalate esters in soil, even though the primary point of entry, (landfills). The migration of phthalate esters out of plastics is slow.

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
dibenzoyl peroxide	LOW (Half-life = 14 days)	LOW (Half-life = 21.25 days)
dicyclohexyl phthalate	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation
dibenzoyl peroxide	LOW (LogKOW = 3.46)
dicyclohexyl phthalate	HIGH (LogKOW = 6.2)

Mobility in soil

Ingredient	Mobility
dibenzoyl peroxide	LOW (Log KOC = 771)
dicyclohexyl phthalate	LOW (Log KOC = 17640)

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal	- Containers may still present a chemical hazard/ danger when empty. - Return to supplier for reuse/ recycling if possible. Otherwise: - If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill. - Where possible retain label warnings and SDS and observe all notices pertaining to the product. - DO NOT allow wash water from cleaning or process equipment to enter drains. - It may be necessary to collect all wash water for treatment before disposal. - In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. - Where in doubt contact the responsible authority. For small quantities of oxidising agent: - Cautiously acidify a 3% solution to pH 2 with sulfuric acid. - Gradually add a 50% excess of sodium bisulfite solution with stirring. - Add a further 10% sodium bisulfite. - If no further reaction occurs (as indicated by a rise in temperature) cautiously add more acid.
------------------------------	--

SECTION 14 Transport information

Labels Required

	
Marine Pollutant	

Land transport (TDG)

14.1. UN number or ID number	3106						
14.2. UN proper shipping name	ORGANIC PEROXIDE TYPE D, SOLID (contains dibenzoyl peroxide)						
14.3. Transport hazard class(es)	<table><tr><td>Class</td><td>5.2</td></tr><tr><td>Subsidiary Hazard</td><td>Not Applicable</td></tr></table>	Class	5.2	Subsidiary Hazard	Not Applicable		
Class	5.2						
Subsidiary Hazard	Not Applicable						
14.4. Packing group	II						
14.5. Environmental hazard	Environmentally hazardous						
14.6. Special precautions for user	<table><tr><td>Special provisions</td><td>16, 38</td></tr><tr><td>Explosive Limit and Limited Quantity Index</td><td>0.5 kg</td></tr><tr><td>ERAP Index</td><td>Not Applicable</td></tr></table>	Special provisions	16, 38	Explosive Limit and Limited Quantity Index	0.5 kg	ERAP Index	Not Applicable
Special provisions	16, 38						
Explosive Limit and Limited Quantity Index	0.5 kg						
ERAP Index	Not Applicable						

Air transport (ICAO-IATA / DGR)

14.1. UN number	3106				
14.2. UN proper shipping name	Organic peroxide type D, solid * (contains dibenzoyl peroxide)				
14.3. Transport hazard class(es)	<table><tr><td>ICAO/IATA Class</td><td>5.2</td></tr><tr><td>ICAO / IATA Subsidiary Hazard</td><td>Not Applicable</td></tr></table>	ICAO/IATA Class	5.2	ICAO / IATA Subsidiary Hazard	Not Applicable
ICAO/IATA Class	5.2				
ICAO / IATA Subsidiary Hazard	Not Applicable				

	ERG Code	5L
14.4. Packing group	Not Applicable	
14.5. Environmental hazard	Environmentally hazardous	
14.6. Special precautions for user	Special provisions	A20 A802
	Cargo Only Packing Instructions	570
	Cargo Only Maximum Qty / Pack	10 kg
	Passenger and Cargo Packing Instructions	570
	Passenger and Cargo Maximum Qty / Pack	5 kg
	Passenger and Cargo Limited Quantity Packing Instructions	Forbidden
	Passenger and Cargo Limited Maximum Qty / Pack	Forbidden

Sea transport (IMDG-Code / GGVSee)

14.1. UN number	3106	
14.2. UN proper shipping name	ORGANIC PEROXIDE TYPE D, SOLID (contains dibenzoyl peroxide)	
14.3. Transport hazard class(es)	IMDG Class	5.2
	IMDG Subsidiary Hazard	Not Applicable
14.4. Packing group	Not Applicable	
14.5. Environmental hazard	Marine Pollutant	
14.6. Special precautions for user	EMS Number	F-J, S-R
	Special provisions	122 274
	Limited Quantities	500 g

14.7. Maritime transport in bulk according to IMO instruments

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code
Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
dibenzoyl peroxide	Not Applicable
dicyclohexyl phthalate	Not Applicable

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
dibenzoyl peroxide	Not Applicable
dicyclohexyl phthalate	Not Applicable

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations and the SDS contains all the information required by the Hazardous Products Regulations.

dibenzoyl peroxide is found on the following regulatory lists

- Canada Categorization decisions for all DSL substances
- Canada Domestic Substances List (DSL)
- International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic
- International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

dicyclohexyl phthalate is found on the following regulatory lists

- Canada Categorization decisions for all DSL substances
- Canada Domestic Substances List (DSL)
- Chemical Footprint Project - Chemicals of High Concern List

Additional Regulatory Information

Not Applicable

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSDL	No (dibenzoyl peroxide; dicyclohexyl phthalate)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes

National Inventory	Status
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	All chemical substances in this product have been designated as TSCA Inventory 'Active'
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	Yes
UAE - Control List (Banned/Restricted Substances)	No (dibenzoyl peroxide; dicyclohexyl phthalate)
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	18/11/2024
Initial Date	15/05/2022

SDS Version Summary

Version	Date of Update	Sections Updated
1.3	18/11/2024	Hazards identification - Classification, Firefighting measures - Fire Fighter (fire/explosion hazard), Composition / information on ingredients - Ingredients

Other information

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

- ▶ PC - TWA: Permissible Concentration-Time Weighted Average
- ▶ PC - STEL: Permissible Concentration-Short Term Exposure Limit
- ▶ IARC: International Agency for Research on Cancer
- ▶ ACGIH: American Conference of Governmental Industrial Hygienists
- ▶ STEL: Short Term Exposure Limit
- ▶ TEEL: Temporary Emergency Exposure Limit,
- ▶ IDLH: Immediately Dangerous to Life or Health Concentrations
- ▶ ES: Exposure Standard
- ▶ OSF: Odour Safety Factor
- ▶ NOAEL: No Observed Adverse Effect Level
- ▶ LOAEL: Lowest Observed Adverse Effect Level
- ▶ TLV: Threshold Limit Value
- ▶ LOD: Limit Of Detection
- ▶ OTV: Odour Threshold Value
- ▶ BCF: BioConcentration Factors
- ▶ BEI: Biological Exposure Index
- ▶ DNEL: Derived No-Effect Level
- ▶ PNEC: Predicted no-effect concentration
- ▶ MARPOL: International Convention for the Prevention of Pollution from Ships
- ▶ IMSBC: International Maritime Solid Bulk Cargoes Code
- ▶ IGC: International Gas Carrier Code
- ▶ IBC: International Bulk Chemical Code

- ▶ AIIC: Australian Inventory of Industrial Chemicals
- ▶ DSL: Domestic Substances List
- ▶ NDSL: Non-Domestic Substances List
- ▶ IECSC: Inventory of Existing Chemical Substance in China
- ▶ EINECS: European INventory of Existing Commercial chemical Substances
- ▶ ELINCS: European List of Notified Chemical Substances
- ▶ NLP: No-Longer Polymers
- ▶ ENCS: Existing and New Chemical Substances Inventory
- ▶ KECI: Korea Existing Chemicals Inventory
- ▶ NZIoC: New Zealand Inventory of Chemicals
- ▶ PICCS: Philippine Inventory of Chemicals and Chemical Substances
- ▶ TSCA: Toxic Substances Control Act
- ▶ TCSI: Taiwan Chemical Substance Inventory
- ▶ INSQ: Inventario Nacional de Sustancias Químicas
- ▶ NCI: National Chemical Inventory
- ▶ FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

The information contained in the Safety Data Sheet is based on our data available on the date of publication. This information is intended to aid the user in controlling the handling risks . It is not to be construed as a warranty or specification of the product quality. The information may not be or may not altogether be applicable to combinations of the product with other substances or to particular applications. The user is responsible for ensuring that appropriate precautions are taken and for satisfying themselves that the data are suitable and sufficient for the intended use of the product . In case of any unclarity we advise consulting the supplier or an expert.